



SPECIFICATIONS:

1. CAPACITY = 3,125 GALLONS WITH 14 $\frac{1}{2}$ " AIR SPACE
2. FULL CAPACITY = 3,755 GALLONS
3. GALLONS PER INCH = 43.4 (AVERAGE)
4. REINFORCING STEEL - GRADE 60
5. CONCRETE: 4,000 PSI MIN.
6. WEIGHT = 24,000 POUNDS
7. MAXIMUM OF 2 FEET OF COVER IN PARKING LOT WITH H15 TRUCK
8. TANK TO MEET ASTM C1227-13 AND ASTM C890-13 REQUIREMENTS
9. MID SEAM CONSTRUCTION
10. JOINT SEALANT: 1" NOMINAL DIAMETER OR EQUIVALENT BUTYL RUBBER MASTIC SEALANT CONTINUOUS IN JOINT.
11. ALL DIMENSIONS SHOW ARE PER ONSITE SEPTIC SOLUTIONS, LLC PRODUCTS 2017.

3,000 GALLON MID SEAM 6" TOP & BOTTOM PRECAST CONCRETE HEAVY DUTY GREASE TRAP

1/2"=1'-0"



BUSINESS PARK AT CAMBRIDGE
CAMBRIDGE, VT. 05444
paul@onsitesepoticsolutions.biz
TEL. 802-644-5500