

- 1. PUMP SHALL BE CAPABLE OF XX GPM @ XX TDH.
- 2. THE CONTRACTOR AND SUPPLIER SHALL COORDINATE POWER REQUIREMENTS PRIOR TO ORDERING OF THE PUMP STATION.
- 3. IF REQUESTED THIS PUMP STATION CAN BE SETUP AS A DUPLEX PUMP STATION.
- 4. PER ONSITE SEPTIC SOLUTIONS, LLC (SUPPLIER), THE TOP OF THIS TANK SHALL BE BURIED NO DEEPER THAN 3 FEET BELOW FINISHED GRADE. IF A DEEPER BURIAL DEPTH IS NEEDED SEE SUPPLIER FOR SIMILAR TANKS THAT CAN BE BURIED DEEPER THAN 3 FEET.
- 5. REFER TO THE PUMP STATION DESIGN BRIEF OR CONSULT THE DESIGNER ON THE NEED FOR A WEEP HOLE OR NOT.

SPECIFICATIONS:

 $\frac{1}{4}$ " WEEP HOLE TO ALLOW FOR FORCEMAIN TO DRAIN BACK CONSULT WITH DESIGNER ON THE NEED OF THE WEEP HOLE

- 1. TANK TO MEET ASTM C-478 REQUIREMENTS
- 2. TOP SEAM CONSTRUCTION
- 3. NOT DESIGNED FOR TRAFFIC AREAS
- 4. ALL DIMENSIONS SHOW ARE PER ONSITE SEPTIC SOLUTIONS, LLC PRODUCTS 2017.



BUSINESS PARK AT CAMBRIDGE CAMBRIDGE, VT. 05444 paul@onsitesepticsolutions.biz TEL. 802-644-5500

48" I.D PUMP STATION

SECTION

8"

1/2"=1-0'

PUMP